

FINAL

**Total Maximum Daily Loads of Fecal Coliform for Restricted
Shellfish Harvesting Areas in the St. Mary's River Basin
in St. Mary's County, Maryland**

FINAL

Prepared by:

Maryland Department of the Environment
Montgomery Business Park Center
1800 Washington Boulevard, Suite 540
Baltimore MD 21230-1718

Submitted to:

Watershed Protection Division
U.S. Environmental Protection Agency, Region III
1650 Arch Street
Philadelphia, PA 19103-2029

September 2004

EPA Submittal Date: September 29, 2005
EPA Approval Date: May 25, 2005

Table of Contents

List of Figures *iii*
List of Tables *iv*
List of Abbreviations *v*
EXECUTIVE SUMMARY..... *vi*
1.0 INTRODUCTION..... *1*
2.0 SETTING AND WATER QUALITY DESCRIPTION..... *1*
 2.1 General Setting *1*
 2.2 Water Quality Characterization *3*
 2.3 Water Quality Impairment..... *13*
 2.4 Nonpoint Source Assessment..... *14*
3.0 TARGETED WATER QUALITY GOAL..... *15*
4.0 TOTAL MAXIMUM DAILY LOADS AND SOURCE ALLOCATION..... *16*
 4.1 Overview..... *16*
 4.2 Analysis Framework..... *16*
 4.3 Critical Condition and Seasonality *18*
 4.4 TMDL Computation..... *18*
 4.5 TMDL Loading Caps *19*
 4.6 Load Allocation..... *20*
 4.7 Margin of Safety *21*
 4.8 Summary of Total Maximum Daily Loads..... *22*
5.0 ASSURANCE OF IMPLEMENTATION..... *22*
6.0 PUBLIC PARTICIPATION..... *24*
REFERENCES..... *25*
Appendix A..... *A1*
Appendix B..... *B1*

List of Figures

Figure 2.1.1: Location Map of St. Mary's River Basin..... 2
Figure 2.1.2: Land Use in the Locust Grove Cove Basin 4
Figure 2.1.3: Land Use in the St. Inigoes Creek Basin..... 5
Figure 2.1.4: Land Use in the Carthegena Creek Basin..... 6
Figure 2.2.1: Shellfish Monitoring Stations in Locust Grove Cove 7
Figure 2.2.2: Observed Fecal Coliform Concentrations at Station 11-04-001B..... 8
Figure 2.2.3: Observed Fecal Coliform Concentrations at Station 11-04-030A 8
Figure 2.2.4: Shellfish Monitoring Stations in St. Inigoes Creek..... 9
Figure 2.2.5: Observed Fecal Coliform Concentrations at Station 11-04-030B..... 10
Figure 2.2.6: Observed Fecal Coliform Concentrations at Station 11-04-032F 10
Figure 2.2.7: Observed Fecal Coliform Concentrations at Station 11-04-706 11
Figure 2.2.8: Observed Fecal Coliform Concentrations at Station 11-04-017 11
Figure 2.2.9: Shellfish Monitoring Stations in the Carthegena Creek..... 12
Figure 2.2.10: Observed Fecal Coliform Concentrations at Station 11-04-017A 13
Figure B-1: Distribution of Septic Systems in the Locust Grove Cove Basin..... B5
Figure B-2: Distribution of Septic Systems in the St. Inigoes Creek Basin B6
Figure B-2: Distribution of Septic Systems in the St. Inigoes Creek Basin B6
Figure B-3: Distribution of Septic Systems in the Carthegena Creek Basin B7
Figure B-4: Diagram to Illustrate Procedure Used to Estimate Fecal Coliform Production from
Estimated Livestock Population B8

List of Tables

Table 2.1.1. Physical Characteristics of St. Mary’s River Restricted Shellfish Harvesting Areas 3
 Table 2.1.2: Land Use Percentage Distribution for Locust Grove Creek (RID 4aB)..... 4
 Table 2.1.3: Land Use Percentage Distribution for St. Inigoes Creek (RID 4aG) 5
 Table 2.1.4: Land Use Percentage Distribution for Carthegenia Creek (RID 4aH) 6
 Table 2.2.1: Location of Shellfish Monitoring Station in Locust Grove Cove..... 7
 Table 2.2.2: Locations of Shellfish Monitoring Stations in St. Inigoes Creek 9
 Table 2.2.3: Locations of Shellfish Monitoring Stations in Carthegenia Creek 12
 Table 2.3.1: St. Mary's River Shellfish Monitoring Stations (1999-2003) - Median and 90th
 Percentile..... 14
 Table 2.4.1: Distribution of Fecal Coliform Source Loads
 in the Locust Grove Cove Basin 15
 Table 2.4.2: Distribution of Fecal Coliform Source Loads in the St. Inigoes Creek Basin..... 15
 Table 2.4.3: Distribution of Fecal Coliform Source Loads in the Carthegenia Creek Basin..... 15
 Table 4.2.1: Drainage Area and Long-Term Flow in St. Mary’s River Basin 18
 Table 4.4.1: Median Loading Analysis of Current Load and Estimated Load Reduction..... 19
 Table 4.4.2: 90th Percentile Analysis of Current Load and Estimated Load Reduction 19
 Table 4.6.1: Load Allocations and Reductions..... 21
 Table A-1: Parameter values required for TMDL calculations for each restricted shellfish
 harvesting area A6
 Table A-2: TMDL calculation results for each restricted shellfish harvesting area A6
 Table B-1: Summary of Nonpoint Sources.....B2
 Table B-2: Wildlife Habitat and Densities.....B2
 Table B-3: Wildlife Fecal Coliform Production RatesB3
 Table B-4: Proportional Population, Households,
 and Septic Systems in St. Mary's RiverB3
 Table B-5: Livestock Fecal Coliform Production Rates.....B9
 Table B-6: Percent of Time Livestock is ConfinedB9
 Table B-7: Distribution of Fecal Coliform Source Loads
 in the Locust Grove Cove BasinB10
 Table B-8: Distribution of Fecal Coliform Source Loads
 in the St. Inigoes Creek Basin.....B10
 Table B-9: Distribution of Fecal Coliform Source Loads
 in the Carthegenia Creek Basin.....B10

List of Abbreviations

BMP	Best Management Practice
CAFO	Confined Animal Feeding Operations
cfs	Cubic Feet per Second
CFR	Code of Federal Regulations
COMAR	Code of Maryland Regulations
CSO	Combined Sewer Overflow
CWA	Clean Water Act
CWP	Center for Watershed Protection
EPA	Environmental Protection Agency
FA	Future Allocation
GIS	Geographic Information System
LA	Load Allocation
LMM	Long-term Moving Median
MACS	Maryland Agricultural Cost Share Program
MASS	Maryland Agricultural Statistic Service
MDE	Maryland Department of the Environment
MDP	Maryland Department of Planning
ml	Milliliter(s)
MOS	Margin of Safety
MPN	Most Probable Number
MRLC	Multi-Resolution Land Cover
MSSCC	Maryland State's Soil Conservation Committee
NPDES	National Pollutant Discharge Elimination System
NSSP	National Shellfish Sanitation Program
RID	MDE Restricted Area Identification
SSO	Sanitary Sewer Overflows
T ⁻¹	Per Tidal Cycle
TARSA	Technical and Regulatory Services Administration
TMDL	Total Maximum Daily Load
USGS	United States Geological Survey
WQIA	Water Quality Improvement Act
WLA	Wasteload Allocation
WQLS	Water Quality Limited Segment
WWTP	Waste Water Treatment Plant

EXECUTIVE SUMMARY

Section 303(d) of the federal Clean Water Act (CWA) and the U.S. Environmental Protection Agency's (EPA) implementing regulations direct each state to identify and list waters, known as water quality limited segments (WQLSs), in which current required controls of a specified substance are inadequate to achieve water quality standards. For each WQLS, the State is to either establish a Total Maximum Daily Load (TMDL) of the specified substance that the waterbody can receive without violating water quality standards, or demonstrate that water quality standards are being met.

St. Mary's River (basin number 02-14-01-03) was first identified on the 1996 303(d) list submitted to the EPA by MDE as being impaired by nutrients, bacteria and sediments, and listings of biological impacts in non-tidal portions and metals added in 2002. On the draft 2004 303(d) List, specific restricted shellfish harvesting areas were identified. This document proposes to establish Total Maximum Daily Loads (TMDL) of fecal coliform at three sites in St. Mary's River (basin number 02-14-01-03), which drains south to the Lower Potomac River: Locust Grove Cove (RID 4aB); St. Inigoes Creek (RID 4aG) and Carthegena Creek (RID 4aH) are located along the St. Mary's River which is along the northern shoreline of the Lower Potomac River. These restricted shellfish harvesting areas are impaired by levels of bacteria exceeding Maryland's water quality standards for fecal coliform, which has resulted in closure of the areas to shellfish harvesting. Fecal coliform is an indicator organism used in water quality monitoring in shellfish waters to indicate fresh sources of pollution from human waste. When the water quality standard for fecal coliform in shellfish waters is exceeded, waters are closed to shellfish harvesting to protect human health due to the potential risk from consuming raw molluscan shellfish from sewage contaminated waters. The water quality goal of these TMDLs is to reduce high fecal coliform concentrations to levels at which the designated uses for these restricted shellfish harvesting areas will be met. The nutrient, sediment and biological impairments will be addressed at a future date.

A variety of data at the watershed scale, including shoreline sanitary survey data, was used to identify potential fecal coliform contributions. The potential fecal coliform contributions were estimated using Geographic Information Systems (GIS) data coverage including land use, septic distribution, property, and stream data, concurrently with local agriculture census data. There are no permitted point source facilities in any of the shellfish areas addressed in this report. From these estimates, the major contributions of fecal coliform load are nonpoint sources, including livestock, wildlife, pets, and failing septic systems. Estimated sources will be revisited once laboratory analysis, using bacteria source tracking, is completed.

A steady state tidal prism model was used to estimate current fecal coliform load based on volume and concentration, and to establish allowable loads for each restricted shellfish harvesting area in St. Mary's River. The tidal prism model incorporates both influences of freshwater discharge and tidal flushing for each area, which thereby represents the hydrodynamics of each selected site. The load is then allocated to sources (human, livestock, pets, and wildlife) by determining the proportional contribution of each source based on animal/source density per land use acre times the fecal coliform production.

FINAL

One of the critical tasks for these TMDLs is to determine current loads from all potential sources in the watershed. The procedure needs to account for temporal variability caused by the seasonal variation and the wet-dry hydrological conditions. In order to accomplish this, data available from the most recent five-year period (i.e., 1999-2003) were used to calculate a median and 90th percentile. These results were then used to estimate the current load condition. The allowable loads for each restricted shellfish harvesting area were then computed using both the median water quality standard for shellfish harvesting of 14 Most Probable Number (MPN)/100ml and the 90th percentile standard of 49 MPN/100ml. An implicit Margin of Safety (MOS) was incorporated into the analysis to account for uncertainty. The TMDLs developed for the restricted shellfish harvesting areas of St. Mary's River Basin for fecal coliform median load and 90th percentile load are as follows:

Locust Grove Cove (RID 4aB):

The median load of fecal coliform TMDL = 1.80×10^{10} counts per day

The 90th percentile of fecal coliform TMDL = 6.28×10^{10} counts per day

St. Inigoes Creek (RID 4aG):

The median load of fecal coliform TMDL = 2.33×10^{11} counts per day

The 90th percentile of fecal coliform TMDL = 8.15×10^{11} counts per day

Carthegena Creek (RID 4aH):

The median load of fecal coliform TMDL = 6.91×10^{10} counts per day

The 90th percentile of fecal coliform TMDL = 2.42×10^{11} counts per day

For the restricted shellfish harvesting areas in St. Mary's River, the 90th percentile criterion requires the greatest reduction. Therefore, the source reduction scenario is developed based on the 90th percentile load TMDL. The source contributions estimated from the watershed analysis were used to determine the percent contribution for each source. The percent distributions of these sources were used to partition the source allocation that would meet water quality standards at restricted shellfish harvesting areas in St. Mary's River. The reduction for each source was calculated based on differences of the current loads and the allowable loads. The reductions needed in each restricted shellfish harvesting area to meet the shellfish criteria and the load allocations required to meet the TMDLs are shown in the table below.

RID	Source	Current Load Distribution (% of Total)	Required Reduction	TMDL Load Allocation (% of Total)
Locust Grove Cove				
4aB	Total	100.0%	84.5%	100.0%
	Wildlife	12.7%	0.0%	81.7%
	Human	0.1%	96.7%	0.0%
	Pets	1.2%	96.7%	0.3%
	Livestock	86.0%	96.7%	18.0%
St. Inigoes Creek				
4aG	Total	100.0%	87.4%	100.0%
	Wildlife	31.7%	70.9%	73.0%
	Human	0.3%	95.0%	0.1%
	Pets	10.1%	95.0%	4.0%
	Livestock	57.9%	95.0%	22.9%
Carthegena Creek				
4aH	Total	100.0%	45.3%	100.0%
	Wildlife	25.9%	0.0%	47.4%
	Human	0.2%	61.2%	0.1%
	Pets	4.2%	61.2%	3.0%
	Livestock	69.7%	61.2%	49.5%

Once the U.S. Environmental Protection Agency (EPA) has approved a TMDL, and it is known what measures must be taken to reduce pollution levels, implementation of best management practices (BMPs) is expected to take place. The Maryland Department of the Environment (MDE) intends for the required reductions to be implemented in an iterative process that first addresses those sources with the largest impact on water quality, with consideration given to ease of implementation and cost. To confirm the bacteria source allocations, MDE is conducting a one-year bacteria source tracking (BST) study for each restricted shellfish harvesting area identified in this report. There is an ongoing effort for continued monitoring by MDE's Shellfish Certification Division.

1.0 INTRODUCTION

Section 303(d)(1)(C) of the federal Clean Water Act (CWA) and the U.S. Environmental Protection Agency's (EPA) implementing regulations direct each State to develop a Total Maximum Daily Load (TMDL) for each impaired water quality limited segment (WQLS) on the Section 303(d) list, taking into account seasonal variations and a protective margin of safety (MOS) to account for uncertainty. A TMDL reflects the total pollutant loading of the impairing substance a water body can receive and still meet water quality standards.

TMDLs are established to achieve and maintain water quality standards. A water quality standard is the combination of a designated use for a particular body of water and the water quality criteria designed to protect that use. Designated uses include activities such as swimming, drinking water supply, and shellfish propagation and harvest. Water quality criteria consist of narrative statements and numeric values designed to protect the designated uses. Criteria may differ among waters with different designated uses.

St. Mary's River (basin number 02-14-01-03) was first identified on the 1996 303(d) list submitted to the EPA by MDE as being impaired by nutrients, bacteria and sediments, and listings of biological impacts in non-tidal portions and metals added in 2002. On the draft 2004 303(d) List, specific restricted shellfish harvesting areas were identified. This document proposes to establish TMDLs of fecal coliform bacteria in St. Mary's River within the Lower Potomac River basin. The nutrient, sediment and biological impairments within the basin will be addressed at a future date.

In both the 1996 and 1998 Maryland 303(d) lists of impaired waterbodies, many 8-digit watersheds were identified as being impaired since these waterbodies are closed to shellfish harvesting due to elevated fecal coliform concentrations. Monitoring is ongoing in shellfish areas, and openings and closings occur routinely. The draft 2004 303(d) List indicates currently restricted shellfish harvesting areas within an 8-digit watershed resolution that require TMDLs.

Fecal coliform are found in the intestinal tract of humans and other warm-blooded animals. Few fecal coliform are pathogenic; however, the presence of elevated levels of fecal coliform in shellfish waters indicate recent sources of pollution. Some common waterborne diseases associated with the consumption of raw clams and oysters harvested from polluted waters include viral and bacterial gastroenteritis and hepatitis A. Fecal coliform may occur in surface waters from point and nonpoint sources.

2.0 SETTING AND WATER QUALITY DESCRIPTION

2.1 General Setting

St. Mary's River is situated approximately 15 km upriver from the mouth of the Potomac River along its northeast shoreline. The shellfish waters include the tidal waters of the St. Mary's River and its tributaries in St. Mary's County, Maryland from the headwaters to its confluence with the Potomac River.




Figure 2.1.1: Location Map of St. Mary's River Basin

Locust Grove Cove (RID 4aB), St. Inigoes Creek (RID 4aG), and Carthegenia Creek (RID 4aH) drain south to the St. Mary's River, as shown in Figure 2.1.1. The drainage basin for St. Mary's River is approximately 12 km in the north-south direction by 4 km in the east-west direction with a drainage area of approximately 32 km². The soils are moderately well-drained with a low water table and good percolation. The soils mainly consist of silt (67.3%), clay (21.5%), and sand (11.2%) (USDA, 1995). The dominant tide in this region is the lunar semi-diurnal (M₂) tide with a tidal range of 0.5 m and tidal period of 12.42 hours. Please refer to Table 2.1.1 for the mean volume and mean water depth of each restricted shellfish harvesting area.

Table 2.1.1. Physical Characteristics of St. Mary's River Restricted Shellfish Harvesting Areas

Restricted Shellfish Harvesting Area (RID)	Mean Water Volume in m³	Mean Water Depth in m
Locust Grove Cove (4aB)	180,161	0.8
St. Inigoes Creek (4aG)	2,371,976	2.1
Carthegenia Creek (4aH)	702,696	1.31

The 2000 Maryland Department of Planning (MDP) land use/land cover data shows that the watershed can be characterized as rural. The land use information for these three shellfish restricted areas in St. Mary's River Basin are shown in Tables 2.1.2 to 2.1.4 and Figures 2.1.2 to 2.1.4. Feedlots identified in the figures are MDP land use types, not permitted confined animal feeding operations (CAFOs).

2.2 Water Quality Characterization

MDE's Shellfish Certification Program is responsible for classifying shellfish harvesting waters to ensure oysters and clams are safe for human consumption. MDE adheres to the requirements of the National Shellfish Sanitation Program (NSSP), with oversight by the U.S. Food and Drug Administration. MDE conducts shoreline surveys and collects routine bacteria water quality samples in the shellfish-growing areas of Maryland. These data are used to determine if the water quality criteria are being met. If the water quality criteria are exceeded, the shellfish areas are closed to harvesting and the designated use is not being achieved.

MDE's Shellfish Certification Division has monitored shellfish growing regions throughout Maryland for the past several decades. There are seven shellfish monitoring stations in the restricted shellfish harvesting areas in St. Mary's River. The monitoring locations and observations recorded during the period 1999-2003 are provided in Tables 2.2.1 to 2.2.3 and Figures 2.2.1 to 2.2.10. In general, based on Statewide shellfish monitoring data, fecal coliform concentrations are higher in the headwaters.

Table 2.1.2: Land Use Percentage Distribution for Locust Grove Creek (RID 4aB)

Land Type	Acreage	Percentage
Urban	47.6	4.7
Forest	363.3	35.8
Agriculture	532.9	52.4
Wetlands	10.1	1.0
Water	61.7	6.1
Totals	1015.6	100.0




Figure 2.1.2: Land Use in the Locust Grove Cove Basin

Table 2.1.3: Land Use Percentage Distribution for St. Inigoes Creek (RID 4aG)

Land Type	Acreage	Percentage
Urban	877.9	18.2
Forest	2541.0	52.7
Agriculture	1110.4	23.0
Wetlands	10.4	0.2
Water	282.1	5.9
Totals	4821.7	100.0




Figure 2.1.3: Land Use in the St. Inigoes Creek Basin

Table 2.1.4: Land Use Percentage Distribution for Carthegena Creek (RID 4aH)

Land Type	Acreage	Percentage
Urban	125.4	7.3
Forest	832.5	48.6
Agriculture	615.9	36.0
Wetlands	5.4	0.3
Water	133.3	7.8
Totals	1712.4	100.0




Figure 2.1.4: Land Use in the Carthegena Creek Basin

Table 2.2.1: Location of Shellfish Monitoring Station in Locust Grove Cove

Shellfish Monitoring Station	Obs. Period	Total Obs.	LATITUDE Deg-min-sec	LONGITUDE Deg-min-sec
11-04-001B	1999-2003	62	38 09 57.0	76 30 26.0




Figure 2.2.1: Shellfish Monitoring Stations in Locust Grove Cove




Figure 2.2.2: Observed Fecal Coliform Concentrations at Station 11-04-001B




Figure 2.2.3: Observed Fecal Coliform Concentrations at Station 11-04-030A

Table 2.2.2: Locations of Shellfish Monitoring Stations in St. Inigoes Creek

Shellfish Monitoring Station	Obs. Period	Total Obs.	LATITUDE Deg-min-sec	LONGITUDE Deg-min-sec
11-04-030A	2001-2003	32	38 09 56.8	76 25 02.3
11-04-030B	2001-2003	32	38 09 53.2	76 24 47.6
11-04-032F	2002-2003	27	38 09 26.0	76 25 39.1
11-04-706	1999-2003	65	38 09 40.0	76 25 43.0




Figure 2.2.4: Shellfish Monitoring Stations in St. Inigoes Creek




Table 2.2.3: Locations of Shellfish Monitoring Stations in Carthegena Creek

Shellfish Monitoring Station	Obs. Period	Total Obs.	LATITUDE Deg-min-sec	LONGITUDE Deg-min-sec
11-04-017	1999-2003	65	38 09 05.0	76 28 16.0
11-04-017A	1999-2003	65	38 09 17.0	76 28 13.0




Figure 2.2.9: Shellfish Monitoring Stations in the Carthegena Creek




Figure 2.2.10: Observed Fecal Coliform Concentrations at Station 11-04-017A

2.3 Water Quality Impairment

The Maryland water quality standards Surface Water Use Designation for these restricted shellfish harvesting areas is Use II - Shellfish Harvesting Waters (Code of Maryland Regulations COMAR 26.08.02.08M). St. Mary's River (basin number 02-14-01-03) has been included on the draft 2004 Integrated 303(d) List as impaired for fecal coliform. These restricted shellfish harvesting areas, located along the northern shoreline of the Lower Potomac River, is identified as areas in this basin that do not meet shellfish water quality standards. Waters within this classification, according to the Code of Maryland Regulation (COMAR) Section 26.08.02.03-3C (criteria for Use II waters - shellfish harvesting) **“means that the median fecal coliform MPN of at least 30 water sample results taken over a three year period to incorporate inter-annual variability shall not exceed 14 per 100 milliliters, and**

(i) In areas affected by point source discharges, not more than 10 percent of the samples shall exceed an MPN of 43 per 100 ml for a five tube decimal dilution test or 49 MPN per 100 ml for a three tube decimal dilution test; or

(ii) In other areas, the 90th percentile of water sample results shall not exceed an MPN of 43 per 100 ml for a five tube decimal dilution test or 49 MPN per 100 ml for a three tube decimal dilution test.”

For this report, the monitoring data averaging period was based on a combination of management objectives and monitoring data requirements for determination of shellfish harvesting area water quality standards attainment. The averaging period for the monitoring data required least 30 samples and used all data within the most recent five year period.

The water quality impairment was assessed using the most recent five-year median and 90th percentile concentrations. Descriptive statistics of the monitoring data and the water quality criterion are shown in Table 2.3.1.

Table 2.3.1: St. Mary's River Shellfish Monitoring Stations (1999-2003) - Median and 90th Percentile

RID	Area Name	Station	Median		90 th Percentile	
			Monitoring Data	Criterion	Monitoring Data	Criterion
			MPN/100ml	MPN/100ml	MPN/100ml	MPN/100ml
4aB	Locust Creek Grove	11-04-001B	39.0	14	315.1	49
4aG	St. Inigoes Creek	11-04-030A	23.0	14	298.9	49
		11-04-030B	41.0	14	499.1	49
		11-04-032F	23.0	14	167.4	49
		11-04-706	3.6	14	27.6	49
4aH	Carthegena Creek	11-04-017	3.6	14	33.1	49
		11-04-017A	9.1	14	70.2	49

2.4 Nonpoint Source Assessment

Nonpoint Source Assessment

Nonpoint sources of fecal coliform bacteria do not have one discharge point but occur over the entire length of a stream or waterbody. There are many types of nonpoint sources in watersheds discharging to the restricted shellfish harvesting areas. The possible introductions of fecal coliform bacteria to the land surface are through the manure spreading process, direct deposition from livestock during the grazing season, and excretions from pets and wildlife. As the runoff occurs during rain events, surface runoff transports water and fecal coliform over the land surface and discharges to the restricted shellfish area. The deposition of non-human fecal coliform directly to the restricted shellfish harvesting area occurs when livestock or wildlife have direct access to the waterbody. Nonpoint source contributions to the bacterial levels from human activities generally arise from failing septic systems and their associated drain fields as well as through pollution from recreation vessel discharges. The transport of fecal coliform from land surface to the restricted shellfish harvesting area is dictated by the hydrology, soil type, land use, and topography of the watershed.

The complete distributions of these source loads are also listed in Tables 2.4.1 to 2.4.3, along with counts/day for each loading. Details of the source estimate procedure can be found in Appendix B. The Bacteria Source Tracking (BST) data will be used to further confirm the source distribution when it becomes available.

Table 2.4.1: Distribution of Fecal Coliform Source Loads in the Locust Grove Cove Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	1.06E+12	86.0%
Pets	1.51E+10	1.2%
Human	7.31E+08	0.1%
Wildlife	1.56E+11	12.7%
Total	1.23E+12	100.0%

Table 2.4.2: Distribution of Fecal Coliform Source Loads in the St. Inigoes Creek Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	1.25E+12	57.9%
Pets	2.17E+11	10.1%
Human	7.04E+09	0.3%
Wildlife	6.83E+11	31.7%
Total	2.15E+12	100.0%

Table 2.4.3: Distribution of Fecal Coliform Source Loads in the Carthegena Creek Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	6.21E+11	69.7%
Pets	3.72E+10	4.2%
Human	1.66E+09	0.2%
Wildlife	2.30E+11	25.9%
Total	8.90E+11	100.0%

Point Source Assessment

There are no permitted point source facilities discharging directly into any of the restricted shellfish harvesting areas , based on the point source permitting information.

3.0 TARGETED WATER QUALITY GOAL

The overall objective of the fecal coliform TMDLs established in this document is to establish the loading caps needed to assure attainment of water quality standards in the restricted shellfish harvesting areas . These standards are described fully in Section 2.3 Water Quality Impairment.

4.0 TOTAL MAXIMUM DAILY LOADS AND SOURCE ALLOCATION

4.1 Overview

This section documents detailed fecal coliform TMDL and source allocation developments for St. Mary's River. The required load reduction was determined based on the most recent five-year data spanning the years 1999 to 2003. The TMDL is presented as counts/day. The second section describes the analysis framework for simulating fecal coliform concentration in areas of the St. Mary's River. The third section addresses the critical period. The fourth section presents the TMDL calculation. The fifth section discusses TMDL loading caps. The sixth section presents the load allocation. The margin of safety is discussed in Section 4.7. Finally, the variables of the equation are combined in a summary accounting of the TMDL.

A TMDL is the total amount of a pollutant that can be assimilated by the receiving water while still achieving water quality criteria, in this case Maryland's water quality criteria for shellfish waters. It is also important to note that the TMDLs presented herein are not literal daily limits. These loads are based on an averaging period that is defined by the water quality criteria (i.e. at least 30 samples). The averaging period used for development of these TMDLs requires at least 30 samples and uses the most recent 5 year period of data..

TMDLs are comprised of the sum of individual wasteload allocations (WLAs) for point sources, load allocations (LAs) for nonpoint sources, and natural background levels. The TMDL must include a margin of safety (MOS), either implicitly or explicitly, that accounts for the uncertainty in the relationship between pollutant loads and the quality of the receiving waterbody, and in the scientific and technical understanding of water quality in natural systems. In addition, the TMDL may include a future allocation (FA) when necessary. Conceptually, this definition is denoted by the equation:

$$\text{TMDL} = \text{WLAs} + \text{LAs} + \text{MOS} + \text{FA}$$

4.2 Analysis Framework

In general, tidal waters are exchanged through their connecting boundaries. The tide and amount of freshwater discharging into the embayment are the dominant influences on the transport of fecal coliform. The methodology used assumes that freshwater input, tidal range, and the first-order decay of fecal coliform are all constant. The TMDL is calculated based on the steady state tidal prism model. Compared to the volumetric method (EPA Shellfish Workshop, 2002), the steady state tidal prism model provides improvements incorporating the influences of tidal induced transport, freshwater, and decay of fecal coliform in the embayment. A detailed description of the model is presented in Appendix A.

FINAL

The most recent five-year median and 90th percentile were used to estimate the current loads. Using the steady state tidal prism model, the loads can be estimated according to the equation as follows (see also Appendix A):

$$L = [C(Q_b + kV) - Q_0C_0] \times Cf \quad (1)$$

where:

L = fecal coliform load (counts per day)

C = fecal coliform concentration (MPN /100ml) of embayment

Q_b = the quantity of mixed water that leaves the embayment on the ebb tide that did not enter the embayment on the previous flood tide (m³ per tidal cycle)

k = the fecal coliform decay rate (per tidal cycle)

V = the mean volume of the embayment (m³)

Q_0 = the quantity of water that enters the embayment on the flood tide through the ocean boundary that did not flow out of the embayment on the previous ebb tide (m³ per tidal cycle)

C_0 = the fecal coliform concentration (MPN/100ml) at the oceanside boundary

Cf = the unit conversion factor.

Q_b and Q_0 are estimated based on the steady state condition as follows:

$$Q_b = Q_0 + Q_f$$

where Q_f is mean freshwater discharge during the tidal cycle

$$Q_0 = \beta Q_T$$

where β is an exchange ratio and Q_T is the total ocean water entering the bay on the flood tide, which is calculated based on tidal range. The dominant tide in this region is the lunar semi-diurnal (M_2) tide with a tidal period of 12.42 hours; therefore, the M_2 tide is used for the representative tidal cycle. In general, the exchange ratio varies from 0.3 to 0.7, based on the previous model tests in Virginia coastal embayments (Kuo et al., 1998; Shen et al., 2002). The observed salinity data were also used to estimate the exchange ratio. The estimated values range from 0.3 to 0.8; therefore, a value of 0.5 is used for the exchange ratio. The stream flow used for the estimation of Q_f was based on the flows of the U.S. Geological Survey (USGS) gage # 02060006, located in Calvert County, MD. For each reported site, the average long-term flow for this USGS gage (i.e., 4.99 cfs) was adjusted by the ratio of the drainage basin area to that of the gage's basin (i.e., 4307.5 acres) to derive estimates of long-term flows. See Table 4.2.1 below.

Table 4.2.1: Drainage Area and Long-Term Flow in St. Mary's River Basin

Restricted shellfish harvesting area (RID)	Drainage Area in Acres	Average Long-Term Flow in cfs
Locust Grove Cove (4aB)	960.30	1.18
St. Inigoes Creek (4aG)	4542.82	5.58
Carthegenia Creek (4aH)	1580.05	1.98

4.3 Critical Condition and Seasonality

The EPA Code of Federal Regulations (40 CFR 130.7 (c)(1)) requires TMDLs to take into account critical conditions for stream flow, loading, and water quality parameters. The intent of this requirement is to ensure that the water quality of the waterbody is protected during times when it is most vulnerable. The critical condition accounts for the hydrologic variation in the watershed over many sampling years whereas the critical period is the condition under which a waterbody is the most likely to violate the water quality standard(s).

The 90th percentile concentration is the concentration exceeded only 10% of the time. Since data collected during the most recent five-year period of data was used to calculate the 90th percentile, the critical condition is implicitly included in the value of the 90th percentile. Given the length of the monitoring record used and the limited applicability of best management practices to extreme conditions, the 90th percentile is utilized instead of the absolute maximum.

A comparison of the median values and the 90th percentile values against the water quality criteria determines which represents the more critical condition or higher percent reduction. If the median values dictate the higher reduction, this suggests that, on average, water sample counts are very high with limited variation around the mean. If the 90th percentile criterion requires a higher reduction, this suggests an occurrence of the high fecal coliform due to the variation of hydrological conditions.

Similar to the critical condition, seasonality is also implicitly included in the analysis due the averaging required in the water quality standards. It is possible that during colder season the bacteria levels will be less however this is not always true when reviewing monitoring data. The shellfish monitoring program uses a systematic random sampling design which was developed to cover inter-annual variability.

4.4 TMDL Computation

According to the water quality standard for fecal coliform in shellfish waters, computation of a TMDL requires analyses of both the median and 90th percentile. These analyses are described below.

For the load analyses, the most recent five-year period of monitoring data (at least 30 sample), specifically fecal coliform concentrations were used to estimate the current loads. This was conducted for median and for 90th percentile conditions. In an area having two or more stations, the station(s) closest to the headwaters were used to represent the restricted shellfish harvesting area concentration, and the downstream station(s) were used to represent boundary conditions. For those restricted shellfish harvesting areas where only one sampling station was available, its median and 90th percentile value served as both the restricted shellfish harvesting area concentration and boundary condition.

The allowable load is calculated using the water quality criteria of a median of 14 MPN/100ml and a 90th percentile of 49 MPN/100ml. The load reductions needed for the attainment of the criteria is determined by subtracting the allowable loads from the current loads. The TMDL calculations are presented in Appendix A. The calculated results are listed in Tables 4.4.1 and 4.4.2.

Table 4.4.1: Median Loading Analysis of Current Load and Estimated Load Reduction

Area	Mean Volume m ³	Fecal Coliform Concentration Median MPN/100mL	Decay Rate per tidal cycle	Estimated Residence Time day	Current Load Counts/day	Allowable Load counts/day	Required Percent Reduction (%)
Locust Grove Cove	180161	39.0	0.36	1.6	1.795E+10	1.795E+10	64.10
St. Inigoes Creek	2371976	23.0	0.36	4.2	2.329E+11	2.329E+11	52.31
Carthegenia Creek	702696	9.1	0.36	2.7	6.912E+10	6.912E+10	0.00

Table 4.4.2: 90th Percentile Analysis of Current Load and Estimated Load Reduction

Area	Mean Volume m ³	Fecal Coliform Concentration 90 th percentile MPN/100mL	Decay Rate per tidal cycle	Estimated Residence Time Day	Current Load counts/day	Allowable Load counts/day	Required Percent Reduction (%)
Locust Grove Cove	180161	315.1	0.36	1.6	4.040E+11	6.282E+10	84.45
St. Inigoes Creek	2371976	298.9	0.36	4.2	6.452E+12	8.152E+11	87.37
Carthegenia Creek	702696	70.2	0.36	2.7	4.425E+11	2.419E+11	45.33

4.5 TMDL Loading Caps

This section presents the TMDL for the median and the 90th percentile conditions. Seasonal variability is addressed implicitly through the interpretation of the water quality standards. The TMDLs for restricted shellfish harvesting areas in St. Mary's River are as follows:

Locust Grove Cove:

The median load of fecal coliform TMDL = 1.80×10^{10} counts per day

The 90th percentile of fecal coliform TMDL = 6.28×10^{10} counts per day

St. Inigoes Creek:

The median load of fecal coliform TMDL = 2.33×10^{11} counts per day

The 90th percentile of fecal coliform TMDL = 8.15×10^{11} counts per day

Carthegena Creek:

The median load of fecal coliform TMDL = 6.91×10^{10} counts per day

The 90th percentile of fecal coliform TMDL = 2.42×10^{11} counts per day

The greater reduction required when comparing the median and the 90th percentile results (see Tables 4.4.1 and 4.4.2), was used for source allocation. It is also important to note that the TMDLs presented herein are not literal daily limits. These loads are based on an averaging period that is defined by the water quality criteria (i.e. at least 30 samples). The averaging period used for development of these TMDLs is five years.

4.6 Load Allocation

The allocations below described in this section demonstrate how the TMDL can be implemented to achieve water quality standards. However, the State reserves the right to revise these allocations provided the allocations are consistent with the achievement of water quality standards.

Source reductions were assigned by first managing controllable sources (human, livestock and pets) and then determining if the TMDL could be achieved. If the total required reduction was not achieved then the wildlife source was then reduced. Given the non-point source characteristics of the wildlife contribution, it was assumed that best management practices applied to controllable sources may also reduced some wildlife sources contributing to the restricted shellfish harvesting area. Based on these assumptions, the source allocation for the watershed for each of the major source categories is estimated. Results are presented in Table 4.6.1.

Table 4.6.1: Load Allocations and Reductions

RID	Source	Current Load Distribution (% of Total)	Required Reduction	TMDL Load Allocation (% of Total)
Locust Grove Cove				
4aB	Total	100.0%	84.5%	100.0%
	Wildlife	12.7%	0.0%	81.7%
	Human	0.1%	96.7%	0.0%
	Pets	1.2%	96.7%	0.3%
	Livestock	86.0%	96.7%	18.0%
St. Inigoes Creek				
4aG	Total	100.0%	87.4%	100.0%
	Wildlife	31.7%	70.9%	73.0%
	Human	0.3%	95.0%	0.1%
	Pets	10.1%	95.0%	4.0%
	Livestock	57.9%	95.0%	22.9%
Carthegena Creek				
4aH	Total	100.0%	45.3%	100.0%
	Wildlife	25.9%	0.0%	47.4%
	Human	0.2%	61.2%	0.1%
	Pets	4.2%	61.2%	3.0%
	Livestock	69.7%	61.2%	49.5%

4.7 Margin of Safety

A Margin of Safety (MOS) is required as part of a TMDL in recognition of many uncertainties in the understanding and simulation of water quality in natural systems. For example, knowledge is incomplete regarding the exact nature and magnitude of pollutant loads from various sources and the specific impacts of those pollutants on the chemical and biological quality of complex, natural water bodies. The MOS is intended to account for such uncertainties in a manner that is conservative from the standpoint of environmental protection.

For TMDL development, the MOS needs to be incorporated to account for uncertainty due to model parameter selection. Based on previous analysis (VIMS, 2004), it was determined that the most sensitive parameter is the decay rate. The value of the decay rate varies from 0.7 to 3.0 per day in salt water (Mancini, 1978; Thomann and Mueller, 1987). A decay rate of 0.7 per day was used as a conservative estimate in the TMDL calculation. Further literature review supports this assumption as a conservative estimate of the decay rate (MDE, 2004). Therefore, the MOS is implicitly included in the calculation.

4.8 Summary of Total Maximum Daily Loads

Since there are no permitted point sources in the watershed, all allocations are to nonpoint sources. The TMDLs are summarized as follows:

The median TMDL (counts per day):

Area	TMDL	=	LA	+	WLA	+	FA	+	MOS
Locust Grove Cove	1.80×10^{10}	=	1.80×10^{10}	+	N/A	+	N/A	+	Implicit
St. Inigoes Creek	2.33×10^{11}	=	2.33×10^{11}	+	N/A	+	N/A	+	Implicit
Carthegena Creek	6.91×10^{10}	=	6.91×10^{10}	+	N/A	+	N/A	+	Implicit

The 90th percentile TMDL (counts per day):

Area	TMDL	=	LA	+	WLA	+	FA	+	MOS
Locust Grove Cove	6.28×10^{10}	=	6.28×10^{10}	+	N/A	+	N/A	+	Implicit
St. Inigoes Creek	8.15×10^{11}	=	8.15×10^{11}	+	N/A	+	N/A	+	Implicit
Carthegena Creek	2.42×10^{11}	=	2.42×10^{11}	+	N/A	+	N/A	+	Implicit

Where:

TMDL = Total Maximum Daily Load
 LA = Load Allocation (Nonpoint Source)
 WLA = Waste Load Allocation (Point Source)
 FA = Future Allocation
 MOS = Margin of Safety

5.0 ASSURANCE OF IMPLEMENTATION

This section provides the basis for reasonable assurances that the fecal coliform TMDL will be achieved and maintained. The appropriate measures to reduce pollution levels in the impaired segments include, where appropriate, the use of better treatment technology or installation of best management practices (BMPs). Details of these methods are to be described in the implementation plan.

In general, MDE intends for the required reductions to be implemented in an iterative process that first addresses those sources with the largest impact on water quality, with consideration given to ease of implementation and cost. The iterative implementation of BMPs in the

watershed has several benefits: tracking of water quality improvements following BMP implementation through follow-up stream monitoring; providing a mechanism for developing public support through periodic updates on BMP implementation; and helping to ensure that the most cost-effective practices are implemented first.

Potential funding sources for implementation include the Maryland's Agricultural Cost Share Program (MACS) which provides grants to farmers to help protect natural resources and the Environmental Quality and Incentives Program which focuses on implementing conservation practices and BMPs on land involved with livestock and production. Additional funding available for local governments include the State Water Quality Revolving Loan Fund and the Stormwater Pollution Cost Share Program. Details of these programs and additional funding sources can be found at <http://www.dnr.state.md.us/bay/services/summaries.html>.

Regulatory enforcement of potential bacteria sources may include MDE's routine sanitary surveys of shellfish growing areas and through National Pollutant Discharge Elimination System (NPDES) permitting activities such as concentrated animal feeding operations (CAFOs). Though not directly linked, it is assumed that the nutrient management plans from the Water Quality Improvement Act of 1998 (WQIA) will have some reduction of bacteria from manure application practices.

As part of Maryland's commitment to the NSSP, will continue to monitor shellfish waters and classify harvesting areas. Those waters meeting shellfish water quality standards may be reclassified as open to harvesting and can serve to track the effectiveness of TMDL implementation and water quality improvements. Additional monitoring will also include bacteria source tracking to confirm the source estimates presented in this document. Bacteria source tracking will be completed according to MDE's schedule posted on MDE's website, http://www.mde.state.md.us:8001/assets/document/BST_schedule.pdf.

Implementation and Wildlife Sources

It is expected that in some waters for which TMDLs will be developed, the bacteria source analysis will indicate that after controls are in place for all anthropogenic sources, the waterbody does not meet water quality standards. However, neither the State of Maryland, nor EPA is proposing the elimination of wildlife to allow for the attainment of water quality standards. This is considered to be an impracticable and undesirable action. While managing the overpopulation of wildlife remains an option for state and local stakeholders, the reduction of wildlife or changing a natural background condition is not the intended goal of a TMDL.

After developing and implementing, to the maximum extent possible, a reduction goal based on the anthropogenic sources identified in the TMDL, Maryland is considering the following TMDL strategy to address wildlife issues. It is possible that implementation to reduce the nonpoint controllable sources may also reduce some wildlife inputs to the shellfish waters. Following this first implementation stage, MDE would re-assess the water quality to determine if the designated use is being achieved. If the water quality standards are not being attained, then MDE would consider developing either a risk based adjusted water quality assessment or a

FINAL

Use Attainability Analysis to reflect the presence of naturally high bacteria levels from uncontrollable sources.

6.0 PUBLIC PARTICIPATION

Public notification of the State's intent to address the bacteria listing was conducted in a variety of ways. Identified stakeholders (including local government contacts, tributary team chairs, and interested parties) were formally notified of MDE's intent to develop bacteria TMDLs in February 2004.

Following this initial contact, these stakeholders were again notified on June 23, 2004 when the document began Interagency Review. The document went through a public comment period from August 11, 2004 to September 9, 2004 where the document was placed in the St. Mary's County Library, MDE's website and notices were published in the St. Mary's Enterprise. Following the public comment period, comments were reviewed and addressed through a comment response document. The documents were then submitted to EPA Region III at which time stakeholders were notified of this action. Once the document was approved by EPA Region III, stakeholders were notified of the action and the finalized document was posted on MDE's website.

REFERENCES

- American Society of Agricultural Engineers (ASAE) (1998). *ASAE Standards, 45th edition:Standards, Engineering Practices, Data*. St. Joseph, MI.
- Brodie, Herbert and Louise Lawrence (1996). Nutrient Sources on Agricultural Lands in Maryland: Final Report of Project NPS 6. Annapolis, MD: Chesapeake Bay Research Consortium.
- Code of Maryland Regulations, 26.08.02.03-3C(1). Bacteriological Criteria for Use II Waters - Shellfish harvesting. Website <http://www.dsd.state.md.us/comar/26/26.08.02.03-3.htm>
- Code of Maryland Regulations (COMAR) 26.08.02.08M.
- De Walle, F.B. (1981). "Failure Analysis of Large Septic Tank Systems." *Journal of Environmental Engineering*. American Society of Civil Engineers.
- Fischer, H.B., List, E.J., Koh, R.C.Y., Imberger, J., and N.H. Brooks (1979): Mixing in inland and coastal water, Academic Press, San Diego.
- Geldrenich, E. and E. A. Kenner. (1969). Concepts of Fecal Streptococci in Stream Pollution. *Journal of Water Pollution Federation*. 41:R336-R352.
- Guo, Q. and G. P. Lordi (2000). "Method for quantifying freshwater input and flushing time in an estuary." *J. of Environmental Engineering*, vol. 126, No. 7, ASCE, 675-683.
- Kator, H. and M.W. Rhodes (1996). Identification of pollutant sources contributing to degraded sanitary water quality in Taskinas Creek National Estuarine research Reserve, Virginia. Special Report in Applied Marine Science and Ocean Engineering No. 336.
- Ketchum, B. H. (1951). "The exchanges of fresh and salt water in tidal estuaries." *J. of Marine Research*, 10(1): 18-38.
- Kuo, A. Y. and B. J. Neilson (1988). A modified tidal prism model for water quality in small coastal embayments. *Water Science Technology*, 20 (6/7): 133-142.
- Kuo, A., Butt, A., Kim, S. and J. Ling (1998). Application of a tidal prism water quality model to Virginia Small Coastal Basins. SRAMSOE No. 348.
- Mancini, J.L. Numerical Estimates of Coliform Mortality Rates Under Various Conditions. *Journal WPCF*, November 2477-2484.

FINAL

Maryland Agricultural Statistic Service (2002a). Agriculture in Maryland 2002 Summary. Annapolis, MD: Maryland Department of Agriculture.

Maryland Agricultural Statistic Service (2002b). Maryland Equine: Results of the 2002 Maryland Equine Census. Annapolis, MD: Maryland Department of Agriculture, the Maryland Horse Industry Board, and the Maryland Agricultural Statistic Service.

Maryland Department of the Environment (2004). Technical Memorandum: Literature Survey of Bacteria Decay Rates.

Maryland Department of Planning. 2000 Reference for Land Use.

Maryland Department of Planning. Estimates of Septic Systems (2003). Baltimore: Maryland Department of Planning, Comprehensive Planning Unit.

Maryland Department of Natural Resources (2003). 2002-2003 Game Program Annual Report. Annapolis: Maryland Department of Natural Resources, Wildlife and Heritage Service. Website:<http://www.dnr.state.md.us/wildlife/>.

Shen, J., H. Wang, and M. Sisson (2002). Application of an Integrated Watershed and Tidal prism Model to the Poquoson Coastal Embayment (submitted to Department of Environmental Quality, Commonwealth of Virginia). Virginia Institute of Marine Science Special Report 380, Gloucester Point, VA.

Swann, C, 1999. A Survey of Residential Nutrient Behaviors in the Chesapeake Bay. Widener Burrows, Inc. Chesapeake Research Consortium. Center For Watershed Protection. Ellicott City, MD. 112 pp.

Thomann, R. V. and J. Mueller (1987). Principles of surface water quality modeling and control. Harper Collins Publishers.

US Department of Commerce. United States Census (2000). Washington DC: US Bureau of the Census.

US Department of Agriculture. (1995). State Soil Geographic (STATSGO) DataBase.

US Department of Agriculture. (1997). Census of Agriculture: Maryland State and County Data. Washington, DC: National Agricultural Statistic Service.

US EPA, Office of Water (2000). Bacteria Indicator Tool User's Guide. EPA-823-B-01-003.

US EPA (2001). Protocol for developing Pathogen TMDLs, EPA 841-R-00-002, Office of Water (4503F), United States Environmental Protection Agency, Washington, DC. 134pp

US EPA Shellfish Workshop Document (2002).

US EPA Stormwater Manager Resource Center. Website: <http://www.stormwatercenter.net/>

FINAL

US EPA Chesapeake Bay Program (1996). Chesapeake Bay Program: Watershed Model Application to Calculate Bay Nutrient Loadings: Final Findings and Recommendations, and Appendices, Annapolis, MD.

VA DEQ (2002) Fecal Coliform TMDL for Dodd Creek Watershed, Virginia, June 2002

VIMS, 2004: Technical Memo for Fecal Coliform TMDL of Shellfish Harvesting areas.

Woods, Helen (2004). Marine Scientist, Virginia Institute of Marine Science. Personal Communication. Gloucester Pt., VA. 2002-2004 various.

Appendix A

Tidal Prism Model

A detailed description of the tidal flushing model is presented in this section. It is assumed that a single volume can represent a water body, and that the pollutant is well mixed in the water body system, as shown in Figure A-1.

The mass balance of water can be written as follows (Guo and Lordi, 2000):

$$\frac{dV}{dT} = (Q_0 - Q_b + Q_f) \quad (1)$$

where Q_0 is the quantity of water that enters the embayment on the flood tide through the ocean boundary (m^3T^{-1}); Q_b is the quantity of mixed water that leaves the bay on the ebb tide that did not enter the bay on the previous flood tide (m^3 per tidal cycle); Q_f is total freshwater input over the tidal cycle (m^3); V is the volume of the bay (m^3); T is the dominant tidal period (hours).

It is further assumed that Q_0 is the pure ocean water that did not flow out of the embayment on the previous ebb tide, and that Q_b is the embayment water that did not enter into the system on the previous flood tide. The mass balance for the fecal coliform can then be written as follows:

$$\frac{dVC}{dT} = Q_0C_0 - Q_bC + L_f + L_l - kVC \quad (2)$$

where L_f is the loading from upstream; L_l is the additional loading from the local area within the tidal cycle, k is the fecal coliform decay rate (or a damped parameter for the net loss of fecal coliform), C is fecal coliform concentration in the embayment, and C_0 is the fecal coliform concentration from outside the embayment.

In a steady-state condition, the mass balance equations for the water and the fecal coliform concentration can be written as follows:

$$Q_b = Q_0 + Q_f \quad (3)$$

$$Q_bC + kVC = Q_0C_0 + L_f + L_l \quad (4)$$

The fecal coliform concentration in the embayment can be calculated as follows:

$$C = \frac{Q_0C_0 + L_f + L_l}{Q_b + kV} \quad (5)$$

FINAL

From Equation (4), assuming $L_f + L_l = Load_t$ and letting C_c be the criterion of fecal coliform in the embayment, the loading capacity can be estimated as:

$$Load_T = C_c(Q_b + kV) - Q_0C_0 \quad (6)$$

The daily load can be estimated based on the dominant tidal period in the area. For the upper Chesapeake Bay the dominant tide is lunar semi-diurnal (M_2) tide with a tidal period of 12.42 hours. If fecal coliform concentration is in MPN/100ml, the daily load (counts day⁻¹) can be estimated as:

$$Load = Load_T \times \frac{24}{12.42} \times 10000 \quad (7)$$

In practice, one may not know Q_0 *a priori*. Instead, one is given the tidal range of the tidal embayment. From that, Q_T , the total ocean water entering the bay on the flood tide, can be calculated. From this, Q_0 , the volume of new ocean water entering the embayment on the flood tide can be determined by the use of the ocean tidal exchange ratio β as:

$$Q_0 = \beta Q_T \quad (8)$$

where β is the exchange ratio and Q_T is the total ocean water entering the bay on the flood tide. The exchange ratio can be estimated from salinity data (Fischer et al., 1979):

$$\beta = \frac{S_f - S_e}{S_0 - S_e} \quad (9)$$

where S_f is the average salinity of ocean water entering the bay on the flood tide, S_e is the average salinity of the bay water leaving the bay, and S_0 is the salinity at the ocean side. The numerical value of β is usually smaller than 1, and it represents the fraction of new ocean water entering the embayment. Once Q_0 is known, then Q_b can be calculated from equation (3).

The residence time, T_L , is an estimate of time required to replace the existing pollutant concentration in a system; it can be calculated as follows:

$$T_L = \frac{V_b}{Q_b} \quad (10)$$

where V_b is mean volume of the embayment. From the definition, the denominator can either be Q_T or Q_b . However, using Q_T assumes that the ocean water enters into the embayment during the flood tide is 100% new, whereas using Q_b takes into consideration that a portion of water is not entirely new. It can be shown that the latter is more realistic. If Q_b is used in the residence time calculation, it will result in a longer time scale than if Q_T is used (Ketchum, 1951; Guo and Lordi, 2000).




Figure A-1: The schematic diagram for the tidal prism model

A Tidal Prism Model Calculation for Locust Grove Cove (RID 4aB)

Case I: The most recent five-year fecal coliform median concentration is used.

The median load calculation is illustrated as follows:

$$\begin{aligned}
 V &= \text{Mean volume of the embayment} = 180160.5(\text{m}^3) \\
 k &= \text{Fecal coliform removal rate} = 0.36(\text{T}^{-1}) \\
 Q_f &= \text{Freshwater discharge} \\
 &= 1.1762 \text{ cfs} = 1.1762 \times 0.0283 \times 86400 \times 12.42 \div 24 = 1488.3 (\text{m}^3\text{T}^{-1}) \\
 Q_0 &= 55960.5 (\text{m}^3\text{T}^{-1}) \\
 Q_b &= 57448.8 (\text{m}^3 \text{T}^{-1}) \\
 C_c &= \text{water quality criterion} = 14 \text{ MPN}/100\text{ml} \\
 C &= \text{current fecal coliform 5-year median concentration} = 39.0 (\text{MPN}/100\text{ml}) \\
 C_0 &= \text{fecal coliform 5-year median outside of the embayment} = 39.0 (\text{MPN}/100\text{ml}) \\
 T &= \text{tidal cycle} = 12.42 \text{ hours} \\
 Cf &= \text{the unit conversion factor}
 \end{aligned}$$

For allowable calculation, C_c is used as fecal coliform concentration (i.e., 14 MPN/100ml). The fecal coliform concentration at the outside of the embayment also uses 14 MPN/100ml. The allowable load is calculated as follows:

$$\begin{aligned}
 \text{Allowable Load} &= \\
 \text{Load} &= [C_c \times (Q_b + kV) - Q_0 \times C_0] \times Cf \\
 &= [14 \times (57448.8 + 0.36 \times 180160.5) - 55960.5 \times 14] \times 24 \div 12.42 \times 10000 \\
 &= 1.795 \times 10^{10}
 \end{aligned}$$

For the current load estimation, the most recent five-year median fecal coliform concentration is used for the calculation. The current load is calculated as follows:

$$\begin{aligned}
 \text{Current condition} &= \\
 \text{Load} &= [C \times (Q_b + kV) - Q_0 \times C_0] \times Cf \\
 &= [(39.0) \times (57448.8 + 0.36 \times 180160.5) - 55960.5 \times (39.0)] \times 24 \div 12.42 \times 10000 \\
 &= 5.000 \times 10^{11}
 \end{aligned}$$

The load reduction is estimated as follows:

$$\begin{aligned}
 \text{Load Reduction} &= \frac{\text{Current Load} - \text{Allowable Load}}{\text{Current Load}} \times 100\% \\
 \text{Load Reduction} &= \frac{5.000 \times 10^{10} - 1.795 \times 10^{10}}{5.000 \times 10^{10}} = 64.1\%
 \end{aligned}$$

A Tidal Prism Model Calculation for Locust Grove Cove (RID 4aB)

Case II: The most recent five-year fecal coliform 90th percentile concentration is used.

The 90th percentile load calculation is illustrated as follows:

$$\begin{aligned}
 V &= \text{Mean volume of the embayment} = 180160.5(\text{m}^3) \\
 k &= \text{Fecal coliform removal rate} = 0.36(\text{T}^{-1}) \\
 Q_f &= \text{Freshwater discharge} \\
 &= 1.1762 \text{ cfs} = 1.1762 \times 0.0283 \times 86400 \times 12.42 \div 24 = 1488.3 (\text{m}^3\text{T}^{-1}) \\
 Q_0 &= 55960.5 (\text{m}^3\text{T}^{-1}) \\
 Q_b &= 57448.8 (\text{m}^3 \text{T}^{-1}) \\
 C_c &= \text{water quality criterion} = 49 \text{ MPN}/100\text{ml} \\
 C &= \text{current fecal coliform 5-year 90}^{\text{th}} \text{ percentile concentration} = 315.13 (\text{MPN}/100\text{ml}) \\
 C_0 &= \text{fecal coliform 5-year 90}^{\text{th}} \text{ percentile at the outside of the embayment} \\
 &= 315.13 (\text{MPN}/100\text{ml}) \\
 T &= \text{tidal cycle} = 12.42 \text{ hours} \\
 Cf &= \text{the unit conversion factor}
 \end{aligned}$$

For allowable calculation, C_c is used as fecal coliform concentration (i.e., 49 MPN/100ml). The fecal coliform concentration at the outside of the embayment also uses 49 MPN/100ml. The allowable load is calculated as follows:

$$\begin{aligned}
 \text{Allowable Load} &= \\
 \text{Load} &= [C_c \times (Q_b + kV) - Q_0 \times C_0] \times Cf \\
 &= [49 \times (57448.8 + 0.36 \times 180160.5) - 55960.5 \times 49] \times 24 \div 12.42 \times 10000 \\
 &= 6.282 \times 10^{10}
 \end{aligned}$$

For the current load estimation, the most recent five-year 90th percentile fecal coliform concentration is used for the calculation. The current load is calculated as follows:

$$\begin{aligned}
 \text{Current condition} &= \\
 \text{Load} &= [C \times (Q_b + kV) - Q_0 \times C_0] \times Cf \\
 &= [(315.13) \times (57448.8 + 0.36 \times 180160.5) - 55960.5 \times (315.13)] \times 24 \div 12.42 \times 10000 \\
 &= 4.040 \times 10^{11}
 \end{aligned}$$

The load reduction is estimated as follows:

$$\begin{aligned}
 \text{Load Reduction} &= \frac{\text{Current Load} - \text{Allowable Load}}{\text{Current Load}} \times 100\% \\
 \text{Load Reduction} &= \frac{4.040 \times 10^{11} - 6.282 \times 10^{10}}{4.040 \times 10^{11}} = 84.45\%
 \end{aligned}$$

Sample calculations load reductions for both the median and 90th percentiles have been presented for the first site in this report (i.e., RID 4aB). The following table lists the parameter values needed for these calculations at all other sites in this report. Please refer to the sample calculations for a full description of each parameter, as well as constants required.

Table A-1: Parameter values required for TMDL calculations for each restricted shellfish harvesting area

St. Mary's River		V	k	Q _r	Q ₀	Q _b	Median		90 th Percentile	
RID	Area Name						C	C ₀	C	C ₀
4aB	Locust Grove Cove	180160.5	0.36	1488.3	55960.5	57448.8	39.0	39	315.1	315.1
4aG	St. Inigoes Creek	2371975.8	0.36	7065.8	282175.8	289241.6	23.0	3.6	298.9	27.6
4aH	Carthegena Creek	702695.7	0.36	2509.4	133895.7	136405.1	9.1	3.6	70.2	33.1

The values attained using the sample calculation are listed below:

Table A-2: TMDL calculation results for each restricted shellfish harvesting area

St. Mary's River		Median			90 th Percentile		
RID	Area Name	Allowable Load	Current Load	Percent Reduction	Allowable Load	Current Load	Percent Reduction
		Counts/day	Counts/day		Counts/day	Counts/day	
4aB	Locust Grove Cove	1.795E+10	5.000E+10	64.10	6.282E+10	4.040E+11	84.45
4aG	St. Inigoes Creek	2.329E+11	4.884E+11	52.31	8.152E+11	6.452E+12	87.37
4aH	Carthegena Creek	6.912E+10	5.9155E+10	0.00	2.419E+11	4.425E+11	45.33

Appendix B

Nonpoint Source Assessment

Nonpoint sources of fecal coliform bacteria do not have one discharge point but occur over the entire length of a stream or waterbody. There are many types of nonpoint sources in watersheds discharging to the restricted shellfish harvesting areas. The possible introductions of fecal coliform bacteria to the land surface are through the manure spreading process, direct deposition from livestock during the grazing season, and excretions from pets and wildlife. As the runoff occurs during rain events, surface runoff transports water and fecal coliform over the land surface and discharges to the restricted shellfish area. The deposition of non-human fecal coliform directly to the restricted shellfish harvesting area occurs when livestock or wildlife have direct access to the waterbody. Nonpoint source contributions to the bacterial levels from human activities generally arise from failing septic systems and their associated drain fields as well as through pollution from recreation vessel discharges. The transport of fecal coliform from land surface to the restricted shellfish harvesting area is dictated by the hydrology, soil type, land use, and topography of the watershed.

In order to determine the sources of fecal coliform contribution and reduction needed to achieve water quality criteria, and to allocate fecal coliform load among these sources, it is necessary to identify all existing sources. The nonpoint source assessment was conducted using available data collected in the watershed. Multiple data sources were used to determine the potential sources of the fecal coliform load from the watershed. The data used for source assessment are:

1. Land use data of 2000 Maryland Department of Planning (MDP) land use/land cover data
2. Livestock inventory by 8-digit Hydrologic Unit Code (Maryland States Soil Conservation Committee (MSSCC); USDA, 1997; MASS, 2002a; MASS, 2002b; Brodie and Lawrence, 1996)
3. GIS 2000 Census of Human population (MDP)
4. Pet survey results from The Center for Watershed Protection (Swann, 1999)
5. Fecal coliform monitoring data (MDE Shellfish Certification Division)
6. The shoreline sanitary survey data (MDE Shellfish Certification Division)
7. Stream GIS coverage (EPA, 1994)
8. Septic GIS Coverage (MDP, 2003)
9. Wildlife population (Maryland DNR, 2003)

In the St. Mary River basin, wildlife contributions, both mammalian and avian, are natural conditions and may represent a background level of bacterial loading. Livestock contributions, such as those from mammalian and avian livestock, mainly result from surface runoff. Pet contributions usually occur through runoff from streets and land. Since there are no direct point source discharges to the embayment and there is a lack of information available for the discharge from boats, it is assumed that human loading results from failures in septic waste treatment systems. The major nonpoint source contributions assessed for restricted shellfish areas in the St. Mary River are summarized in Table B-1. The potential nonpoint sources were grouped into four categories: wildlife; human; pets; and livestock. Due to insufficient data sources, the source

assessment method does not account for boat discharge, resuspension from bottom sediment, and the potential for regrowth of fecal coliform in the embayment.

Table B-1: Summary of Nonpoint Sources

Category	Source
Wildlife	Beaver, deer, goose, duck, muskrat, raccoon and wild turkey
Human	Septic
Pets	Dog
Livestock	cattle, sheep, chicken, and horse

A. Wildlife Contributions

In general it is assumed that the wildlife species existent in the watershed include beaver, deer, goose, duck, muskrat, raccoon and wild turkey. Fecal coliform from wildlife can be from excretion on land that is subject to runoff or direct deposition into the stream. Wildlife populations within the watershed were estimated based on a combination of information from the Maryland DNR Wildlife and Heritage Service and from habitat information listed in Virginia bacteria TMDL report (VA DEQ, 2002). Habitat density results were reviewed by the Maryland Department of Natural Resources, and are listed in Table B-2.

Table B-2: Wildlife Habitat and Densities

Wildlife Type	Population Density	Habitat Requirements
Beaver ¹	4.8 animals/ mile of stream	Tidal and non-tidal regions
Deer ²	0.047 animals/acre	Entire watershed
Goose ²	0.087 animals/acre	Entire watershed
Duck ²	0.039 animals/acre	Entire watershed
Muskrat ¹	2.75 animals/acre	Within 66 feet of streams and ponds
Raccoon ¹	0.07 animals/acre	Within 600 feet of streams and ponds
Wild Turkey ¹	0.01 animals/acre	Entire watershed excluding farmsteads and urban

¹ VA DEQ (2002); ²MD DNR (2003)

The habitat areas for each species were determined using ArcView GIS with the 2000 MDP land use data and EPA reach coverage in the watershed. The GIS tool was applied to the land use coverage to create a habitat area according to Table B-2. For the deer, goose and duck estimates the entire watershed was used because the density estimates were developed using watershed area as the ratio estimator. Wildlife populations were obtained by applying assumed wildlife densities to these extracted areas. The populations of the wildlife were obtained by applying density factors to estimated habitat areas. The fecal coliform contributions were estimated based on the estimated number of wildlife and fecal coliform production rates, which are listed in Table B-3. To obtain the total wildlife contribution, population density is multiplied by the applicable acreage or stream mile and that product is multiplied by fecal coliform production rates for each animal.

Table B-3: Wildlife Fecal Coliform Production Rates

Source	Fecal Coliform Production (counts/animal/day)
Beaver ¹	2.50E+08
Deer ¹	5.00E+08
Goose ²	2.43E+09
Duck ¹	2.43E+09
Muskrat ³	3.40E+07
Raccoon ³	1.00E+09
Wild turkey ⁴	9.30E+07

¹USEPA (2000); ²Use duck rate (USEPA, 2000);
³Kator and Rhodes (1996); ⁴ASAE (1998)

B. Human Contributions

Human loading can result from failures in septic waste treatment systems or through pollution from recreation vessel discharges in the identified restricted shellfish harvesting areas. It is assumed that the failing of a septic system is a direct load contribution from humans. The estimation of human contribution is based on human population, properties, the number of septic systems in the watershed, and an estimated septic system failure rate.

The human population and the number of households were estimated from the GIS 2000 Census Block that includes the St. Mary's River watershed. Since the subwatersheds throughout the Lower Potomac River Basin are sub-areas of the Census Block, the GIS tool was used to extract these areas from the 2000 Census Block. The percentage of the subwatershed area relative to the total area of the 2000 Census Block was calculated. This percentage was applied to partition the total census block population and the total census block number of households to proportion the population within the area of the sub-watersheds. The results are shown in Table B-4.

Table B-4: Proportional Population, Households, and Septic Systems in St. Mary's River

RID	Area Name	Proportional Population	Proportional Septic Systems	Proportional Households
4aB	Locust Grove Cove	92	48	32
4aG	St. Inigoes Creek	1,135	695	460
4aH	Carthegenia Creek	209	164	79

The distributions of septic systems in the identified restricted shellfish harvesting areas of the St. Mary's River are shown in Figures B-1 to B-3. Based on GIS property coverage, a point is assumed to represent a septic system. The total number of septic systems in each reported basin is shown in Table B-4. The total number of septic systems in the watershed can be estimated based on total points in the GIS property coverage.

It is assumed that the human contribution is attributed to septic systems. The human contribution to the restricted shellfish harvesting areas was calculated using the number of septic systems, the average number of people using the septic systems, and the failure rate of the septic systems. The estimated fecal coliform loading from humans is calculated as follows:

$$\text{Load} = P S F_r C Q C_v$$

Where

P = number of people per septic system

S = number of septic systems in the restricted area

F_r = failure rate of septic systems

C = fecal coliform concentration of wastewater

Q = daily discharge of wastewater per person

C_v = unit conversion factor (37.854)

The number of people using each septic system is estimated by the ratio of the population to the number of septic systems. According to shoreline sanitary survey data in the St. Mary's River watershed, an estimated failing rate of 3% was used for the total number of failing septic systems. This rate is in the same range as that in the upper Chesapeake Bay (De Walle, 1981; EPA Stormwater Management Center). It was assumed that wastewater for each person was 70 gallons per day with a fecal coliform concentration of 1×10^5 most probable number (MPN)/100ml. The estimated load due to failures of septic systems is less than 1%.

C. Pet Contributions

Pet contributions usually occur through runoff from either an urban or a low-density residential area. Dogs are the only domestic pets assumed to contribute fecal coliform. Dog license information can be obtained from the county, however, these data will not include feral or unlicensed pets. This is likely to cause an underestimation of the total population. Therefore, the dog populations for sites in the St. Mary's River watershed were estimated based on the number of households (see Table B-4). According to a survey conducted by the Center for Watershed Protection of Chesapeake Bay residents, about 41% of the households own a dog. Of these dog owners, only about 56% walk their dogs, and of that group only 59% clean up most of the time (i.e., 41% do not). The estimated total load available for wash off is 23% (i.e., $56\% \times 41\%$). The fecal coliform contribution from the dog population was estimated using a production rate of 5×10^9 counts/dog/day (EPA, 2000). The estimated load contribution from pets is about 1%, 3%, and 1%, respectively, at Locust Grove Cove, St. Inigoes Creek, and Carthegena Creek. Using the estimated populations from Table B-4, simple calculations of estimated fecal coliform loading from dogs in the St. Mary's River watershed are shown below:

FINAL

$$\text{LOADING}_{\text{dog}} = P R_1 R_2 R_3 \text{PR}_{\text{dog}}$$

where:

P = number of households in specified restricted area

R₁ = ratio of dogs per household in this region

R₂ = percentage of owners that walk their dogs

R₃ = percentage of walked dogs contributing fecal

PR_{dog} = average fecal coliform production rate for dogs




Figure B-1: Distribution of Septic Systems in the Locust Grove Cove Basin




Figure B-2: Distribution of Septic Systems in the St. Inigoes Creek Basin





Figure B-3: Distribution of Septic Systems in the Carthegena Creek Basin

D. Livestock Contributions

The fecal coliform contribution from livestock is through the manure spreading processes and direct deposition during grazing. This contribution was estimated based on land use data and the Maryland livestock census data (Brodie and Lawrence, 1996; USDA, 1997; MASS, 2002). Animal ratio estimators for the 8-digit watersheds were developed based on the finest resolution of animal counts available – statewide, region or county. These Maryland 8-digit watershed livestock animal counts were then proportioned to the sub-watersheds using the procedure outlined in Figure B-4. The fecal coliform load was estimated based on the total number of livestock and the fecal coliform production rates.

Figure B-4: Diagram to Illustrate Procedure Used to Estimate Fecal Coliform Production from Estimated Livestock Population



Fecal coliform production rates used to estimate loading are listed in Table B-5. The estimated fecal coliform produced by animals was divided into manure spreading and direct deposition, depending on the percent of time they were confined. The percent of time livestock was confined is listed in Table B-6. The estimated percentage of manure available for wash off is about 40%(VIMS, 2004). For chickens, however, only about 10% is available for wash off (Woods, 2004). Therefore, fecal coliform decay is also considered in the estimation of fecal coliform production. The percent of fecal coliform available for wash off from manure spreading in the field is also listed in Table B-6.

Table B-5: Livestock Fecal Coliform Production Rates

Source	Fecal Coliform Production (counts/animal/day)
Dairy	1.01E+11
Beef	1.20E+10
Horses	4.20E+08
Sheep	1.20E+10
Broilers	1.36E+08
Turkeys	9.30E+07
Chickens	1.36E+08
Layers	1.36E+08
Hogs	1.08E+10

US EPA (2000)

Table B-6: Percent of Time Livestock is Confined

Livestock	Percent of time confined	Percent Manure Available For Wash off
Dairy	80.0%	40.0%
Beef	20.0%	40.0%
Horses	50.0%	40.0%
Sheep	50.0%	40.0%
Broilers	85.0%	10.0%
Turkeys	85.0%	10.0%
Chickens	85.0%	10.0%
Layers	85.0%	10.0%
Hogs	100.0%	40.0%

US EPA (1996); Woods (2004)

E. Nonpoint Source Summary

The complete distributions of these source loads are also listed in Tables B-7 to B-9, along with counts/day for each loading. The BST data will be used to further confirm the source distribution when it becomes available.

Table B-7: Distribution of Fecal Coliform Source Loads in the Locust Grove Cove Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	1.06E+12	86.0%
Pets	1.51E+10	1.2%
Human	7.31E+08	0.1%
Wildlife	1.56E+11	12.7%
Total	1.23E+12	100.0%

Table B-8: Distribution of Fecal Coliform Source Loads in the St. Inigoes Creek Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	1.25E+12	57.9%
Pets	2.17E+11	10.1%
Human	7.04E+09	0.3%
Wildlife	6.83E+11	31.7%
Total	2.15E+12	100.0%

Table B-9: Distribution of Fecal Coliform Source Loads in the Carthegena Creek Basin

Fecal Coliform Source	Loading Counts/day	Loading Percent
Livestock	6.21E+11	69.7%
Pets	3.72E+10	4.2%
Human	1.66E+09	0.2%
Wildlife	2.30E+11	25.9%
Total	8.90E+11	100.0%